

# Atlas Copco Generators

## Designed to perform, built to last



## QAS 250- 330 (60 Hz)



### Durability

- Rugged Zincor steel coated canopy.
- Mounted on rugged skids.
- Designed for extreme weather conditions.
- A standard sealed spillage-free frame, which will ensure that all fluids can be retained within the frame.

### Efficiency

- Increased up-time: carefully selected components and tested configuration.
- Genuine versatility: QAS 250 and QAS 330 can power a wide variation of critical applications.
- Reduced cost of ownership: 500 hrs service intervals, efficient transport handling.
- Designed for easy servicing.

### Health, Safety and Environment

Atlas Copco's stringent manufacturing standards follow ISO 9001 quality assurance regulations. All components are produced and tested to exacting standards for optimum performance in the most demanding conditions.

*Sustainable Productivity*

**Atlas Copco**

# Technical Data

Model	QAS 250	QAS 330
Rated Standby Power	203 kW / 253 kVA	294 kW / 367 kVA
Rated Prime Power	183 kW / 228 kVA	264 kW / 330 kVA
Voltage Selections 3Ø	208 / 240 / 480	208 / 240 / 480
Amperage Capacity @ 208 volts 3Ø	600 amps	900 amps
Amperage Capacity @ 240 volts 3Ø	550 amps	794 amps
Amperage Capacity @ 480 volts 3Ø	275 amps	397 amps
Sound Pressure Level @ 23 feet @ 75% load	74 dB(A)	74 dB(A)
Fuel Tank Capacity (w/trailer)	450 gal.	450 gal.
Fuel Consumption @ 75% load	9.21	13.4
Fuel Autonomy @ 75% load	48.8 hr.	33.6 hr.

Engine	John Deere	John Deere
Model	6090HFG94	6090HFG95
Rated Speed	1800 rpm	1800 rpm
Emission Compliance	EPA Interim Tier 4	EPA Interim Tier 4
Rated Output	318 HP @ 1800 rpm	433 HP @ 1800 rpm
Coolant	Water / Glycol	Water / Glycol
Cylinders	6	6
Displacement	9 L	9 L
Engine Control	Electronic	Electronic

Alternator	Leroy Somer	Leroy Somer
Model	LSA 46.2 M5	LSA 46.2 L9
Degree Of Protection / Insulation Class	IP23 / H	IP23 / H

Dimensions and Weight	
Dimensions Skid (L x W x H)	153 x 53 x 90 in.
Weight - Skid Wet	10,098 lbs / 10,498 lbs
Dimensions Trailer (L x W x H)	217 x 87 x 108 in.
Weight - Trailer Wet	13,459 lbs / 13,859 lbs

Convenience Receptacles	
20 amp - 125 volt GFCI duplex	2
50 amp - 125 / 250 volt twist lock	2

The information contained herein is general in nature and is not intended for specific construction, installation or application purposes.

## U.S. Sales/Distribution Center

### Atlas Copco Compressors LLC

1800 Overview Drive  
 Rock Hill, SC 29730  
 Tel. 803-817-7438  
 Tel. 800-232-3234  
 Fax. 803-817-7450  
 www.atlascopco.us

Generator Features and Options Include	
Multi-Voltage Selector Switch	●
Remote Start / Stop	●
Digital Control System	●
110% Fluid Containment	●
Skid-Mount	○
Battery Charger	○
Electronic Governor	●
Coolant Heater	●
Spare Tire	○
Rear Stabilizer Jacks	○
Tool Box	○
External Fuel Connections	●

Option: ○ Standard: ●



## Control Panel

A comprehensive instrument panel enables all key operating functions to be supervised without opening the canopy. Analog gauges provide at-a-glance monitoring. Protected by a tough transparent cover, the single panel provides easy start up and control of the generator. The panel also provides full system monitoring to ease operation.



Use only authorized parts. Warranty or Product Liability does not cover any damage or malfunction caused by the use of unauthorized parts.

www.atlascopco.com